

# QSFP28 100G COHERENT DWDM CMIS HIGH TX POWER

QSFP28, 100GBASE-ZR/OTU4 Coh 50/100GHz Tunable 120km, 30dB, CMIS5.2, LC, Tx=0dBm

## TQ2031-TUNX-SO

The TQ2031-TUNx-SO is a pluggable QSFP28 DWDM transceiver designed for high capacity 100 Gigabit Ethernet (100GbE) Data Center Interconnect (DCI) optical communication applications up to 120km unamplified or 300km amplified links. The TQ2031-TUNx-SO has an on-board dispersion compensation that can handle chromatic dispersion up to 2 400ps/nm (~120km), or 6 000ps/nm (~300km) with "Extended mode" over a singlemode fiber.

The transceiver utilizes a tunable DP-QPSK modulated 28 Gbps wavelength with ability to be tuned with either 50GHz or 100GHz spacing enabling up to 96 channels over a 50GHz DWDM grid system as specified in the ITU-T 694.1 standard. The module provides two types of integrated FEC: Staircase FEC (SC-FEC) and RS(255,239) FEC. The transceiver also includes an EDFA, enabling a Tx power of 0dBm.

The electrical signals are transmitted and received from the host via a standard 38 pin connector described in the QSFP28 MSA (SFF-8679). The electrical interface is compliant to CAUI-4 (IEEE P802.3bm Annex 83E), splitting the 100Gbps signal into four parallel 25 Gbps NRZ streams as well as OTU4 (ITU-T 100G OTN).

The management interface specification of the module is compliant to CMIS5.2. For SFF-8636 compliant version, see p/n: TQ2032-TUNC-SO. The transceiver is also available in C-temp version covering a temperature range of 0°C to +70°C (TQ2031-TUNC-SO) and I-temp version covering -40°C to +85°C (TQ2031-TUNI-SO).

## TECHNICAL DATA

Parameter	Value
Technology	DWDM QSFP28 100GBASE-ZR
Transmission media	SM (2x LC)
Typical reach, unamplified	120km <sup>1)</sup>
Typical reach, amplified	120km <sup>2)</sup> 300km <sup>3)</sup>
Nominal wavelength	191.35 – 196.10 THz (96ch)
Bit rate support	103.12Gbps
Protocol support	100GbE/OTU4
Dispersion tolerance	±2400ps/nm; ±6000ps/nm <sup>3)</sup>
Power budget	0 – 30dB
Power consumption	< 6.2W (TQ2031-TUNC-SO) <sup>3)</sup> < 6.7W (TQ2031-TUNI-SO) <sup>3)</sup>
Operating temperature	0°C to +70°C (TQ2031-TUNC-SO) -40°C to +85°C (TQ2031-TUNI-SO)
Storage temperature	-40°C to +85°C

<sup>1)</sup> Limited by power budget

<sup>2)</sup> Limited by dispersion compensation

<sup>3)</sup> Extended mode, set through the host when the transceiver is in Low Power mode. The Extended mode will increase the worst-case power consumption with 0.3W.

<sup>4)</sup> Average power

<sup>5)</sup> Receiver Sensitivity at unamplified configurations; OSNR >35dB/0.1nm

<sup>6)</sup> 100G DQPSK SC-FEC

<sup>7)</sup> 100G DQPSK RS-FEC

<sup>8)</sup> Extended range; Rx signal input power range over which performance can be guaranteed with <1dB OSNR penalty relative to Rx OSNR tolerance limit

Parameter	Value
<b>Transmitter data:</b>	
Output power per lane	Min: 0dBm <sup>4)</sup>
Tx output monitor range	-2dBm to +4dBm <sup>4)</sup>
Transmit wavelength	191.35 – 196.10 THz
Tx OSNR, in-band	39dB/12.5GHz
Tx OSNR, out-of-band	30dB/12.5GHz
<b>Receiver data:</b>	
Minimum input power, unamplified	-30.0dBm <sup>4) 5) 6)</sup> -24.0dBm <sup>4) 5) 7)</sup>
Minimum input power, amplified	-18dBm <sup>4)</sup> -22dBm <sup>4) 8)</sup>
Overload (max power)	3.0dBm <sup>4)</sup>
OSNR Tolerance	16.5 dB/0.1nm <sup>6)</sup> 21.5 dB/0.1nm <sup>7)</sup>
Rx power monitor range	Signal power: -21dBm to +3dBm Total power: -21dBm to +6dBm
Wavelength range	191.35 – 196.10 THz
Misc	Remote Diagnostic Monitoring Flextune™
MSA compliance	SFF-8665, -8661, -8679 CMIS5.2 / OIF C-CMIS-01.2

### Safety/regulatory compliance:

TUV/UL/FDA (contact Smartoptics for latest certification information)

RoHS compliance

### Media FEC

SC-FEC

RS-FEC

### Latency [µs]

17

3

Subject to change without notice.

For more information visit [smartoptics.com](http://smartoptics.com).

smartoptics

## ORDERING INFORMATION

Ordering code	Description
TQ2031-TUNC-SO	QSFP28, 100GBASE-ZR/OTU4 Coh 50/100GHz Tunable 120km, w/o TOF, 30dB, CMIS5.2, LC
TQ2031-TUNI-SO	QSFP28, 100GBASE-ZR/OTU4 Coh 50/100GHz Tunable 80km, w/o TOF, 30dB, CMIS5.2, LC, I-temp

## GENERAL DEFINITIONS

Parameter	Description
Technology	Grey; Transceiver type for non-WDM applications. Electrical or optical. CWDM; Transceiver type for CWDM applications using G.694.2 channel grid. DWDM; Transceiver type for DWDM applications using G.694.1 channel grid. BiDi; Transceiver pair using two different wavelength channels operating on a single-fiber. DAC: Direct Attach Cable. Electrical cable with attached connectors. AOC: Active Optical Cable. Optical cable with attached connectors.
Transmission Media	Type of fiber, e.g. Multimode (MM) or Singlemode (SM). Number of and connector type within brackets (e.g. 2x LC, 1x MPO).
Typical reach	Nominal distance performance based on typical fiber dispersion, fiber loss and power budget properties, i.e. w/o dispersion compensation and optical amplification. Actual distance is dependent on actual optical path loss and dispersion properties.
Bit rate range	Supported bit rate range in Gigabit or Megabit per second (Gbps or Mbps).
Protocols	Protocols within supported bit rate range.
Nominal wavelength	Typical wavelength(s) from transmitter.
Interface standards	Referenced interface standards or MSA's, e.g. IEEE 802.3 standard for 10GbE services or 100G 4WDM-10 etc.
Power budget	Min and max power budget between Transmitter and Receiver w/o optical path penalties.
Dispersion tolerance/penalty	Maximum amount of tolerated dispersion and required reduction of power budget to maintain stipulated Bit Error Rate (BER) and at a given bit rate.
Temperature range	Max operating case temperature range. Standard temperature range (C-temp): 0°C to +70°C (32°F to +158°F) Extended temperature range (E-temp): typically -20°C to +75°C (-4°F to +167°F) Industrial temperature range (I-temp): -40°C to +85°C (-40°F to +185°F)
Power consumption	Worst case power consumption. Will vary over temperature.
Transmitter Output power	Average output power. Provided in min and max values.
Receiver minimum input power	Minimum average input power at specified BER, normally $1E^{-12}$ . Note that some protocols require FEC to achieve sufficient BER.
Receiver max input power	Maximum average input power giving a BER, normally $1E^{-12}$ .
DDM	Digital Diagnostic Monitoring functionality as defined in e.g. SFF-8472 MSA.

Smartoptics makes no warranties or representations, expressed or implied, of any kind relative to the information or any portion thereof contained in this document or its adaptation or use, and assumes no responsibility or liability of any kind, including, but not limited to, indirect, special, consequential or incidental damages, for any errors or inaccuracies contained in the information or arising from the adaptation or use of the information or any portion thereof. The information in this document is subject to change without notice.